


CP8L32(I.S)



1.5 sq.mm Push in 8 level internally shorted compact Terminal Blocks

8 level marshelling internally shorted Terminal Block. The space saving method for potential and signal distribution. The push in technology for easy wiring connection i.e. the stripped wire is simply inserted into the terminal point.

TECHNICAL DATA

Rated Voltage	250 V
Rated Current	8 A
Housing Material	Polymide
Standard Colour	Grey
Product Function	Select
Wire Entry Orientation	Top
Mounting Possibility	DIN 35/DIN 35-15 Rail
Rated Surge Voltage	8 KV
Pollution Degree	3

CONNECTION DATA

Conductor Cross Section Stranded min.	0.2 mm ²
Conductor Cross Section Stranded max.	1.5 mm ²
Conductor Cross Section AWG/Kcmil min	24 AWG
Conductor Cross Section AWG/Kcmil max	14 AWG
Stripping Length	8 mm

DIMENSIONS

Height with DIN 35 x 15 mm rail	91.5 mm
Height with DIN 35 x 7.5 mm rail	84 mm
Length	120 mm
Width (Thickness)	9 mm

ORDERING INFORMATION

CAT. NO.	DESCRIPTION	STD. PACK
CP8L32(I.S)	1.5 sq.mm 8 level Marshelling internally shorted Terminal Block in Grey colour	50

ACCESSORIES

IMAGES	CAT. NO.	DESCRIPTION	STD. PACK
	CA701-1M	Din 35 Rail unslotted 1 meter	50
	CA701-2M	Din 35 Rail unslotted 2 meter	50
	CA701-2M-S	Din 35 Rail slotted 2 meter	50
	CA701-1M-S	Din 35 Rail slotted 1 meter	50
	CA701-15-1M	Din 35 Rail 15 deep unslotted 1 meter	50
	CA701-15-1M-S	Din 35 Rail 15 deep slotted 1 meter	50
	CA701-15-2M	Din 35 Rail 15 deep unslotted 2 meter	50
	CA701-15-2M-S	Din 35 Rail 15 deep slotted 2 meter	50


ACCESSORIES

IMAGES	CAT. NO.	DESCRIPTION	STD. PACK
	CA103	EndClamp in Polyamide suitable for Din 35/Din 35-15 rails	50
	CA104	EndClamp in Polyamide suitable for Din 35/Din 35-15 rails	50
	CA202	End Clamp in Polyamide suitable for Din 35 / Din 35-15 Rails	25
	CA509/K3.5V	Marking Tag Blank suitable for separator plate of CP8L32 & CP8L32(I.S)	100
	CA509/K9	Blank Marking Tag	100
	SPCP8L32	Separator Plate in Grey colour	10

APPROVALS



CP8L32(I.S)



connectwell
THE RIGHT CONNECTION

RATINGS AS PER STANDARDS

STANDARDS	UL 1059	CSA C.22.2 No:158	IEC/EN60947-7-1
Approvals	UL	CSA	CE
Conductor Cross Section Stranded min.	24 AWG	24 AWG	0.2 mm ²
Conductor Cross Section Stranded max.	14 AWG	14 AWG	1.5 mm ²
Rated Voltage	300 V	300 V	250 V
Rated Current	10 A	10 A	8 A