


# CYDLGF4FT



**connectwell**  
THE RIGHT CONNECTION

4 sq.mm Double Level + ground Terminal Block in Grey colour.

These blocks are ideal for use in application requiring high density wiring. Interconnection shorting is possible at both levels. The CYDLGF4FT is a double level terminal block with as additional connection point for earthing (Grounding) cables. This separate connection point is appropriately identified by the green yellow imprint on its top.

## TECHNICAL DATA

Rated Voltage	500 V
Rated Current	32 A
Tightening Torque	0.5 Nm
Housing Material	Polymide
Standard Colour	Grey
Product Function	Double Level Plus Earthing
Wire Entry Orientation	side
Mounting Possibility	DIN 35/DIN 35-15 Rail
Operated by	screw driver
Rated Surge Voltage	6 KV
Pollution Degree	3

## CONNECTION DATA

Conductor Cross Section Stranded min.	0.2 mm <sup>2</sup>
Conductor Cross Section Stranded max.	4 mm <sup>2</sup>
Conductor Cross Section AWG/Kcmil min	24 AWG
Conductor Cross Section AWG/Kcmil max	10 AWG
Conductor Cross Section Stranded with Ferrule/Lug min	0.2 mm <sup>2</sup>
Conductor Cross Section Stranded with Ferrule/Lug max	4 mm <sup>2</sup>
2 Conductors with same Cross Section Stranded min	0.2 mm <sup>2</sup>
2 Conductor with same Cross Section Stranded max	1.5 mm <sup>2</sup>
Conductor Cross Section Solid min	0.2 mm <sup>2</sup>
Conductor Cross Section Solid max	6 mm <sup>2</sup>
Stripping Length	9 mm

## DIMENSIONS

Height with DIN 35 x 15 mm rail	75.1 mm
Height with DIN 35 x 7.5 mm rail	67.6 mm
Length	94.5 mm
Width (Thickness)	6 mm

## ORDERING INFORMATION

CAT. NO.	DESCRIPTION	STD. PACK
CYDLGF4FT	4 sq.mm double level grounding Terminal Block in Grey colour	50


## ACCESSORIES

IMAGES	CAT. NO.	DESCRIPTION	STD. PACK
	CA701-1M	Din 35 Rail unslotted 1 meter	50
	CA701-2M	Din 35 Rail unslotted 2 meter	50
	CA701-2M-S	Din 35 Rail slotted 2 meter	50
	CA701-1M-S	Din 35 Rail slotted 1 meter	50
	CA701-15-1M	Din 35 Rail 15 deep unslotted 1 meter	50
	CA701-15-1M-S	Din 35 Rail 15 deep slotted 1 meter	50
	CA701-15-2M	Din 35 Rail 15 deep unslotted 2 meter	50
	CA701-15-2M-S	Din 35 Rail 15 deep slotted 2 meter	50
	CA702	End Clamp in Polyamide 66 suitable for Din 32 / Din 35 / Din 35-15 Rails	50
	CA202	End Clamp in Polyamide suitable for Din 35 / Din 35-15 Rails	25
	JX4/2	Shorting Link for 6 mm wide TB	100
	JX4/3	Shorting Link for 6 mm wide TB	50
	JX4/4	Shorting Link for 6 mm wide TB	50
	JX4/5	Shorting Link for 6 mm wide TB	50
	JX4/8	Shorting Link for 6 mm wide TB	10
	JX4/10	Shorting Link for 6 mm wide TB	10
	JX4/16	Shorting Link for 6 mm wide TB	10
	CA509/K6	Blank Marking Tag	100
	SCS0.6/3.5	Electricians Screwdriver for slotted screws	10

## APPROVALS



CYDLGF4FT



**connectwell**  
THE RIGHT CONNECTION

**RATINGS AS PER STANDARDS**

STANDARDS	IEC 60947-7-1	UL 1059	CSA C.22.2 No:158
Approvals	CE	UL	CSA
Conductor Cross Section Stranded min.	0.2 mm <sup>2</sup>	24 AWG	24 AWG
Conductor Cross Section Stranded max.	4 mm <sup>2</sup>	10 AWG	10 AWG
Rated Voltage	500 V	300 V	300 V
Rated Current	32 A	30 A	30 A
Tightening Torque	0.4 Nm	4.5 lb-in	4.5 lb-in