


CXDLG2.5/2B/ I.S



connectwell
THE RIGHT CONNECTION

pluggable feed through Spring Clamp Ground Terminal Block Internally shorted in Green Yello colour

The Spring Clamp is operated by using a screw driver to provide an access to the wire through an opening in the spring clamp. The inserted wire gets clamped on to the current bar when the screw driver is removed. One side can be plugged with CX2.5PN plugs.

TECHNICAL DATA

Housing Material	Polymide
Standard Colour	Grey
Product Function	Double Level
Wire Entry Orientation	Top
Mounting Possibility	DIN 35/DIN 35-15 Rail
Operated by	Screw Driver
Rated Surge Voltage	8 KV
Pollution Degree	3

CONNECTION DATA

Conductor Cross Section Stranded min.	0.2 mm ²
Conductor Cross Section Stranded max.	2.5 mm ²
Conductor Cross Section AWG/Kcmil min	24 AWG
Conductor Cross Section AWG/Kcmil max	12 AWG
Conductor Cross Section Stranded with Ferrule/Lug min	0.2 mm ²
Conductor Cross Section Stranded with Ferrule/Lug max	2.5 mm ²
Conductor Cross Section Solid min	0.2 mm ²
Conductor Cross Section Solid max	4 mm ²
2 Conductors with same Cross Section Stranded with TWIN Ferrule/Lug min	0.2 mm ²
2 Conductor with same Cross Section Stranded with TWIN Ferrule/Lug max	1.0 mm ²
Stripping Length	10 mm

DIMENSIONS

Height with DIN 35 x 15 mm rail	57 mm
Height with DIN 35 x 7.5 mm rail	49.5 mm
Length	78 mm
Width (Thickness)	5 mm

ORDERING INFORMATION

CAT. NO.	DESCRIPTION	STD. PACK
CXDLG2.5/2B/I.S	2.5 sq.mm pluggable double level Spring Clamp Ground Terminal Block Internally Shorted	50


ACCESSORIES

IMAGES	CAT. NO.	DESCRIPTION	STD. PACK
	CA701-1M	Din 35 Rail unslotted 1 meter	50
	CA701-2M	Din 35 Rail unslotted 2 meter	50

ACCESSORIES

IMAGES	CAT. NO.	DESCRIPTION	STD. PACK
	CA701-2M-S	Din 35 Rail slotted 2 meter	50
	CA701-1M-S	Din 35 Rail slotted 1 meter	50
	CA701-15-1M	Din 35 Rail 15 deep unslotted 1 meter	50
	CA701-15-1M-S	Din 35 Rail 15 deep slotted 1 meter	50
	CA701-15-2M	Din 35 Rail 15 deep unslotted 2 meter	50
	CA701-15-2M-S	Din 35 Rail 15 deep slotted 2 meter	50
	CA103	EndClamp in Polyamide suitable for Din 35/Din 35-15 rails	50
	CA104	EndClamp in Polyamide suitable for Din 35/Din 35-15 rails	50
	EPCXDL2.5/2B	End Plate in Grey Colour	50
	JX2.5/2	Shorting Link for 2.5 sq mm series	100
	JX2.5/3	Shorting Link for 2.5 sq mm series	50
	JX2.5/4	Shorting Link for 2.5 sq mm series	50
	JX2.5/5	Shorting Link for 2.5 sq mm series	50
	JX2.5/6	Shorting Link for 2.5 sq mm series	50
	JX2.5/7	Shorting Link for 2.5 sq mm series	10
	JX2.5/8	Shorting Link for 2.5 sq mm series	10
	JX2.5/10	Shorting Link for 2.5 sq mm series	10
	CA509/K5	Blank Marking Tag	100
	WLX2.5	Warning label suitable for 5mm wide terminal block	50
	SCS0.5/3	Electricians Screwdriver for slotted screws	10
	CXPOLN	Coding Pin	25

CXDLG2.5/2B/
I.S



connectwell
THE RIGHT CONNECTION

ACCESSORIES

APPROVALS

IMAGES	CAT. NO.	DESCRIPTION	STD. PACK
	CX2.5PN	2.5 mm ² 1 POLE PLUG SPRING CLAMP TB	100
	CX2.5PNBU	2.5 mm ² 1 POLE PLUG SPRING CLAMP TB IN BLUE COLOR	100
	CX2.5PNYG	2.5 mm ² 1 POLE PLUG SPRING CLAMP TB IN YELLOW GREEN COLOR	100
	CX2.5PLN	2.5 mm ² 1 POLE PLUG SP CL STACK END TB	100
	CX2.5PN/2	2.5 mm ² 2 POLE PLUG SPRING CLAMP TB	100
	CX2.5PN/3	2.5 mm ² 3 POLE PLUG SPRING CLAMP TB	100
	CX2.5PN/4	2.5 mm ² 4 POLE PLUG SPRING CLAMP TB	100
	CX2.5PN/5	2.5 mm ² 5 POLE PLUG SPRING CLAMP TB	100
	CX2.5PN/6	2.5 mm ² 6 POLE PLUG SPRING CLAMP TB	25
	CX2.5PN/7	2.5 mm ² 7 POLE PLUG SPRING CLAMP TB	25
	CX2.5PN/8	2.5 mm ² 8 POLE PLUG SPRING CLAMP TB	25
	CX2.5PN/9	2.5 mm ² 9 POLE PLUG SPRING CLAMP TB	25
	CX2.5PN/10	2.5 mm ² 10 POLE PLUG SPRING CLAMP TB	25
	CX2.5PN/11	2.5 mm ² 11 POLE PLUG SPRING CLAMP TB	10
	CX2.5PN/12	2.5 mm ² 12 POLE PLUG SPRING CLAMP TB	10
	CX2.5PN/13	2.5 mm ² 13 POLE PLUG SPRING CLAMP TB	10
	CX2.5PN/14	2.5 mm ² 14 POLE PLUG SPRING CLAMP TB	10
	CX2.5PN/15	2.5 mm ² 15 POLE PLUG SPRING CLAMP TB	10

	CP2.5P	CP2.5P - 2.5 mm ² 1 Pole Push In Connection Plug	50
	CP2.5PL	CP2.5PL - 2.5 mm ² 1 Pole Push In Connection End Plug	50


	CXLPN	Locking Pin for CX2.5PN/CX2.5SN	25
--	-------	---------------------------------	----

	TX2.5	2.5mm ² TEST PLUG	20
--	-------	------------------------------	----

	TM5	Flexible Marker Carrier for double level Terminal Block	50
--	-----	---------------------------------------------------------	----



CXDLG2.5/2B/
I.S



RATINGS AS PER STANDARDS

STANDARDS	UL 1059	IEC/EN60947-7-1	
Conductor Cross Section Stranded min.	24 AWG	0.2 mm ²	
Conductor Cross Section Stranded max.	12 AWG	2.5 mm ²	