


CPDL1.5(I.S)



connectwell
THE RIGHT CONNECTION

1.5 sq.mm Multiple Connection Internally Shorted Terminal Blocks with 4 connection points.

These blocks are used to connect multiple wires in single Terminal Block, thereby eliminating reliability problems encountered when connecting multiple wires in a single clamp.

TECHNICAL DATA

Rated Voltage	500 V
Rated Current	15 A
Housing Material	Polymide
Standard Colour	Grey
Product Function	Double Level
Wire Entry Orientation	Top
Mounting Possibility	DIN 35/DIN 35-15 Rail
Rated Surge Voltage	8 KV
Pollution Degree	3

CONNECTION DATA

Conductor Cross Section Stranded min.	0.2 mm ²
Conductor Cross Section Stranded max.	1.5 mm ²
Conductor Cross Section AWG/Kcmil min	24 AWG
Conductor Cross Section AWG/Kcmil max	14 AWG
Conductor Cross Section Stranded with Ferrule/Lug min	0.2 mm ²
Conductor Cross Section Stranded with Ferrule/Lug max	1.0 mm ²
2 Conductors with same Cross Section Stranded min	0.2 mm ²
2 Conductor with same Cross Section Stranded max	1 mm ²
Conductor Cross Section Solid min	0.2 mm ²
Conductor Cross Section Solid max	1.5 mm ²
Stripping Length	8 mm

DIMENSIONS

Height with DIN 35 x 15 mm rail	52.8 mm
Height with DIN 35 x 7.5 mm rail	45.3 mm
Length	67.2 mm
Width (Thickness)	3.5 mm

ORDERING INFORMATION

CAT. NO.	DESCRIPTION	STD. PACK
CPDL1.5(I.S)	1.5 sq.mm 2 level Internally shorted Terminal Block	50
CPDL1.5(I.S)BU	1.5 sq.mm 2 level Internally Shorted Terminal Block in Blue Colour	50


ACCESSORIES

IMAGES	CAT. NO.	DESCRIPTION	STD. PACK
	CA701-1M	Din 35 Rail unslotted 1 meter	50
	CA701-2M	Din 35 Rail unslotted 2 meter	50
	CA701-2M-S	Din 35 Rail slotted 2 meter	50
	CA701-1M-S	Din 35 Rail slotted 1 meter	50
	CA701-15-1M	Din 35 Rail 15 deep unslotted 1 meter	50
	CA701-15-1M-S	Din 35 Rail 15 deep slotted 1 meter	50
	CA701-15-2M	Din 35 Rail 15 deep unslotted 2 meter	50
	CA701-15-2M-S	Din 35 Rail 15 deep slotted 2 meter	50
	CA103	EndClamp in Polyamide suitable for Din 35/Din 35-15 rails	50
	CA104	EndClamp in Polyamide suitable for Din 35/Din 35-15 rails	50
	JX1.5/2	Shorting Link for 1.5 sq mm series	100
	JX1.5/3	Shorting Link for 1.5 sq mm series	50
	JX1.5/4	Shorting Link for 1.5 sq mm series	50
	JX1.5/10	Shorting Link for 1.5 sq mm series	10
	EPCPD1.5	End Plate in Grey Colour	50
	MS3.5	Marking Tag Blank suitable for 3.5mm Terminal Blocks	100
	TM3.5	Flexible Marker Carrier for 3.5 mm thick double level Terminal Block	50

APPROVALS



CPDL1.5(I.S)



connectwell
THE RIGHT CONNECTION

RATINGS AS PER STANDARDS

STANDARDS	UL 1059	CSA C.22.2 No:158	IEC/EN60947-7-1
Approvals	UL	CSA	CE
Conductor Cross Section Stranded min.	24 AWG	24 AWG	0.2 mm ²
Conductor Cross Section Stranded max.	14 AWG	14 AWG	1.5 mm ²
Rated Voltage	300 V	300 V	500 V
Rated Current	15 A	15 A	15 A