


# CPDLK2.5



**connectwell**  
THE RIGHT CONNECTION

2.5 sq.mm knife disconnecting Push in double level compact Terminal block.

CP series Push In type Terminal Block are the next generation, compact Terminal Blocks. The new CP series terminals have a much wider range for wire terminations. The Push button on the top is to be pressed for using flexible cable without lug for connections. Lugged cable can be directly pressed into clamp to make connections..Disconnection is achieved by opening the insulated knife (blade) contact in the middle of the terminal.

## TECHNICAL DATA

Rated Voltage	500 V
Rated Current	16 A
Housing Material	Polymide
Standard Colour	Grey
Product Function	Knife Type Disconnect and Test
Wire Entry Orientation	Top
Mounting Possibility	DIN 35/DIN 35-15 Rail
Rated Surge Voltage	6 KV
Pollution Degree	3

## CONNECTION DATA

Conductor Cross Section Stranded min.	0.2 mm <sup>2</sup>
Conductor Cross Section Stranded max.	2.5 mm <sup>2</sup>
Conductor Cross Section AWG/Kcmil min	24 AWG
Conductor Cross Section AWG/Kcmil max	12 AWG
Stripping Length	10 mm

## DIMENSIONS

Height with DIN 35 x 15 mm rail	57.5 mm
Height with DIN 35 x 7.5 mm rail	50 mm
Length	107.25 mm
Width (Thickness)	5 mm

## ORDERING INFORMATION

CAT. NO.	DESCRIPTION	STD. PACK
CPDLK2.5	2.5 sq.mm Knife Disconnecting Push in Terminal Block in Grey colour	100

## ACCESSORIES

IMAGES	CAT. NO.	DESCRIPTION	STD. PACK
	CA701-1M	Din 35 Rail unslopped 1 meter	50
	CA701-2M	Din 35 Rail unslopped 2 meter	50
	CA701-2M-S	Din 35 Rail slopped 2 meter	50
	CA701-1M-S	Din 35 Rail slopped 1 meter	50
	CA701-15-1M	Din 35 Rail 15 deep unslopped 1 meter	50
	CA701-15-1M-S	Din 35 Rail 15 deep slopped 1 meter	50
	CA701-15-2M	Din 35 Rail 15 deep unslopped 2 meter	50
	CA701-15-2M-S	Din 35 Rail 15 deep slopped 2 meter	50


## ACCESSORIES

IMAGES	CAT. NO.	DESCRIPTION	STD. PACK
	CA103	EndClamp in Polyamide suitable for Din 35/Din 35-15 rails	50
	CA104	EndClamp in Polyamide suitable for Din 35/Din 35-15 rails	50
	JX2.5/2	Shorting Link for 2.5 sq mm series	100
	JX2.5/3	Shorting Link for 2.5 sq mm series	50
	JX2.5/4	Shorting Link for 2.5 sq mm series	50
	JX2.5/5	Shorting Link for 2.5 sq mm series	50
	JX2.5/6	Shorting Link for 2.5 sq mm series	50
	JX2.5/7	Shorting Link for 2.5 sq mm series	10
	JX2.5/8	Shorting Link for 2.5 sq mm series	10
	JX2.5/10	Shorting Link for 2.5 sq mm series	10
	CA509/K4	Blank Marking Tag	100
	MS5	Marking Tag Blank suitable for CXM2.5 / CXMG2.5 Terminal Blocks	100
	SCS0.5/3	Electricians Screwdriver for slotted screws	10
	EPCPDLK2.5	End Plate	50

## APPROVALS



CPDLK2.5



**connectwell**  
THE RIGHT CONNECTION

RATINGS AS PER STANDARDS

STANDARDS	UL 1059	CSA C.22.2 No:158	IEC/EN60947-7-1
Approvals	UL	CSA	CE
Conductor Cross Section Stranded min.	24 AWG	24 AWG	0.2 mm <sup>2</sup>
Conductor Cross Section Stranded max.	12 AWG	12 AWG	2.5 mm <sup>2</sup>
Rated Voltage	300 V	300 V	500 V
Rated Current	14 A	14 A	16 A