


CSTSN6



connectwell
THE RIGHT CONNECTION

M6 sized Stud Type Terminal Blocks, suitable for operation with nut driver.

These Terminal Blocks are preferred for applications where the connections are subjected to severe vibrations.

The wire is crimped to ring /fork type Lug (Ferrule) and is screwed on to flat current bar on the Terminal Block .The range includes Terminal Blocks for wire sizes from 1.5 to 35 sq mm.

Cross connection can be achieved with the aid of external shorting links.

It is recommended to use Protective Covers in transparent plastic to fully shroud these assemblies.

TECHNICAL DATA

Rated Voltage	1000 V
Rated Current	125 A
Tightening Torque	3 Nm
Housing Material	Melamine
Product Function	Feed Through
Wire Entry Orientation	Side Entry
Mounting Possibility	DIN 32 Rail
Stud Size	M6
Operated by	Nut Driver
Rated Surge Voltage	8 KV
Pollution Degree	3

CONNECTION DATA

Conductor Cross Section Stranded min.	1.5 mm ²
Conductor Cross Section Stranded max.	35 mm ²
Conductor Cross Section AWG/Kcmil min	22 AWG
Conductor Cross Section AWG/Kcmil max	2 AWG
Conductor Cross Section Stranded with Ferrule/Lug min	1.5 mm ²
Conductor Cross Section Stranded with Ferrule/Lug max	35 mm ²
2 Conductors with same Cross Section Stranded min	1.5 mm ²
2 Conductor with same Cross Section Stranded max	16 mm ²
Conductor Cross Section Solid min	1.5 mm ²
Stripping Length	12 mm

DIMENSIONS

Height with DIN 32 rail	47.5 mm
Length	50 mm
Width (Thickness)	17 mm


ORDERING INFORMATION

CAT. NO.	DESCRIPTION	STD. PACK
CSTSN6	35 sq.mm Stud Type Terminal Block in Khaki/Beige colour	100
CSTSN6R	35 sq.mm Stud Type Terminal Block in Red colour	100
CSTSN6Y	35 sq.mm Stud Type Terminal Block in Yellow colour	100
CSTSN6BU	35 sq.mm Stud Type Terminal Block in Blue colour	100
CSTSN6BK	35 sq.mm Stud Type Terminal Block in Black colour	100







ACCESSORIES

IMAGES	CAT. NO.	DESCRIPTION	STD. PACK
	CA501-1M	Din 32 Rail unslotted 1 meter	50
	CA501-1M-S	Din 32 Rail slotted 1 meter	50
	CA501-2M	Din 32 Rail unslotted 2 meter	50
	CA501-2M-S	Din 32 Rail slotted 2 meter	50
	CA502	End Clamp in Steel suitable for Din 32 Rail	50
	CA702	End Clamp in Polyamide 66 suitable for Din 32 / Din 35 / Din 35-15 Rails	50
	CSTSEP2	End Plate in Khaki / Beige colour	50
	CSTSPP	Partition Plate in Khaki / Beige colour	50
	CA514/7-2	Insulated Removable Shorting Link available in 2 Pole	100
	CA514/7-3	Insulated Removable Shorting Link available in 3 Pole	50
	CA514/7-4	Insulated Removable Shorting Link available in 4 Pole	50

CSTSN6


connectwell
 THE RIGHT CONNECTION

ACCESSORIES

IMAGES	CAT. NO.	DESCRIPTION	STD. PACK
	CA514/8-2	Insulated Ring Type Shorting Link available in 2 Pole	100
	CA514/8-3	Insulated Ring Type Shorting Link available in 3 Pole	50
	CA514/8-4	Insulated Ring Type Shorting Link available in 4 Pole	50
	CA512/7-2	Fork Type Shorting Link available in 2 Pole	100
	CA512/7-3	Fork Type Shorting Link available in 3 Pole	50
	CA512/7-4	Fork Type Shorting Link available in 4 Pole	50
	CA512/8-2	Ring Type Shorting Link available in 2 Pole	100
	CA512/8-3	Ring Type Shorting Link available in 3 Pole	50
	CA512/8-4	Ring Type Shorting Link available in 4 Pole	50
	CA509/K2B4	Blank Marking Tag	100
	CSTSPC1-2	Protective cover is available in 100 mm Length	10
	CSTSPC1-3	Protective cover is available in 200 mm Length	10
	CSTSPC1-4	Protective cover is available in 300 mm Length	10
	CSTSPC1	This protective cover is used for covering 2 Terminals	100
	CSTSPC1-1	This protective cover is used for covering 3 Terminals	100

APPROVALS



RATINGS AS PER STANDARDS

STANDARDS	CSA C.22.2 No:158	IEC/EN60947-7-1
Approvals	CSA	CE
Conductor Cross Section Stranded min.	22 AWG	1.5 mm ²
Conductor Cross Section Stranded max.	2 AWG	35 mm ²
Rated Voltage	600 V	1000 V
Rated Current	125 A	125 A
Tightening Torque	25 lb-in	3 Nm