

CTS2.5M



connectwell
THE RIGHT CONNECTION

2.5 sq.mm Standard Feed Through Terminal Blocks

2.5 sq.mm Feed Through Terminal Blocks are the most Versatile terminals for control, Automation, Instrumentation and Power Distribution applications. These Terminal Block are ideal choice for use in High Temperature applications.

These Terminal Blocks can be mounted on standard rail and available for wire sizes 0.25 to 2.5 sq mm. These Terminal Blocks have marker holding recesses to accept marking tags for circuit identification. Cross connection can be achieved with the aid of shorting links / sleeves & screws. The specially designed Knock Out at the centre must be removed to facilitate Permanent shorting.

TECHNICAL DATA

Rated Voltage	800 V
Rated Current	24 A
Tightening Torque	0.4 Nm
Housing Material	Melamine
Product Function	Feed Through
Wire Entry Orientation	Side Entry
Mounting Possibility	DIN 32 Rail
Screw Size	M2.5
Operated by	Screwdriver
Rated Surge Voltage	8 KV
Pollution Degree	3

CONNECTION DATA

Conductor Cross Section Stranded min.	0.2 mm ²
Conductor Cross Section Stranded max.	2.5 mm ²
Conductor Cross Section AWG/Kcmil min	22 AWG
Conductor Cross Section AWG/Kcmil max	12 AWG
Conductor Cross Section Stranded with Ferrule/Lug min	0.2 mm ²
Conductor Cross Section Stranded with Ferrule/Lug max	2.5 mm ²
2 Conductors with same Cross Section Stranded min	0.2 mm ²
2 Conductor with same Cross Section Stranded max	1.5 mm ²
Conductor Cross Section Solid min	0.2 mm ²
Conductor Cross Section Solid max	4 mm ²
2 Conductors with same Cross Section Stranded with TWIN Ferrule/Lug min	0.2 mm ²
2 Conductor with same Cross Section Stranded with TWIN Ferrule/Lug max	1.5 mm ²
Stripping Length	9 mm
Internal Cylindrical Gauge	A3

DIMENSIONS

Height with DIN 32 rail	46.5 mm
Length	36.5 mm
Width (Thickness)	6 mm


ORDERING INFORMATION

CAT. NO.	DESCRIPTION	STD. PACK
CTS2.5M	2.5 sq.mm Feed Through Terminal Block in Khaki/Beige colour	200
CTS2.5MR	2.5 sq.mm Feed Through Terminal Block in Red colour	200
CTS2.5MY	2.5 sq.mm Feed Through Terminal Block in Yellow colour	200
CTS2.5MBU	2.5 sq.mm Feed Through Terminal Block in Blue colour	200
CTS2.5MBK	2.5 sq.mm Feed Through Terminal Block in Black colour	200

ACCESSORIES

IMAGES	CAT. NO.	DESCRIPTION	STD. PACK
	CA501-1M	Din 32 Rail unslotted 1 meter	50
	CA501-1M-S	Din 32 Rail slotted 1 meter	50
	CA501-2M	Din 32 Rail unslotted 2 meter	50
	CA501-2M-S	Din 32 Rail slotted 2 meter	50
	CA502	End Clamp in Steel suitable for Din 32 Rail	50
	CA702	End Clamp in Polyamide 66 suitable for Din 32 / Din 35 / Din 35-15 Rails	50
	CTSEP01	End Plate in Khaki / Beige colour	50
	CTSP01	Partition Plate in Khaki / Beige colour	50
	CA521/2	Pre assembled Shorting Link for 2 way shorting.	100
	CA521/3	Pre assembled Shorting Link for 3 way shorting.	100
	CA521/4	Pre assembled Shorting Link for 4 way shorting.	100
	CA521/10	Pre assembled Shorting Link for 10 way shorting.	10

CTS2.5M



connectwell
THE RIGHT CONNECTION

ACCESSORIES


IMAGES	CAT. NO.	DESCRIPTION	STD. PACK
	CA621/2	Insulated Pre Assembled Shorting Links 2 way shorting	100
	CA621/3	Insulated Pre Assembled Shorting Links 3 way shorting	100
	CA621/4	Insulated Pre Assembled Shorting Links 4 way shorting	100
	CA621/10	Insulated Pre Assembled Shorting Links 10 way shorting	10
	CA503/01	Permanent Shorting Link for 2 way shorting	100
	CA504/01	Permanent Shorting Link for 3 way shorting	100
	CA505/01	Permanent Shorting Link for 4 way shorting	100
	CA510/01	Permanent Shorting Link for 10 way shorting	100
	CA507/S/Q/01	Shorting Sleeve and Screw suitable for CTS2.5(M) Terminal Block	100
	CA507/S/01	Short Sleeve & Screw for Permanent shorting link	100
	CA506/01	Removable Shorting link suitable for CTS2.5(M)	100
	CA507/L/Q/01	Long Shorting Sleeve and Screw suitable for CTS2.5(M) Terminal Block	100
	CA507/L/01	Long Stud & Screw for Temporary shorting link	100
	CA509/K2	Marking Tag Blank suitable for CDL4U / CDL4U(I.S) / CTL2.5U / CTL2.5UH / CTL2.5UL / CTL2.5HUL / CTL2.5U(I.S) / CTL2.5U(I.S)D2 / CGMT4 / CSFL4U / CSFL4U(L) / CMT4 / CMB4 / ASF4 / ASF4(L) / CTS2.5(100
	CA707/TS/04	Test Socket Suitable for CTS2.5(M), CTS2.5	1
	SCS0.5/3	Electricians Screwdriver for slotted screws	10

APPROVALS

RATINGS AS PER STANDARDS

STANDARDS	CSA C.22.2 No:158	IEC/EN60947-7-1	IEC 60947-7-1
Approvals	CSA	CE	S MARK
Conductor Cross Section Stranded min.	22 AWG	0.2 mm ²	0.5 mm ²
Conductor Cross Section Stranded max.	12 AWG	2.5 mm ²	2.5 mm ²

CTS2.5M



connectwell
THE RIGHT CONNECTION

RATINGS AS PER STANDARDS

Rated Voltage	600 V	800 V	800 V
Rated Current	25 A	24 A	24 A
Tightening Torque	7 lb-in	0.4 Nm	0.4 Nm