


PTB300SH



connectwell
THE RIGHT CONNECTION

300 sq.mm Stud Type Power Terminal Blocks

PTB series Terminal Blocks are preferred for application using wires of large cross section. The Wire is crimped to a ring / fork lug and is screwed on to the flat current bar of the Terminal Block. Specially designed Mounting Feet holds the Terminal Block rigidly on to the Mounting Rail. Two Lugs of the rated cross section can be connected to the Terminal Block, without sacrificing the safety of the Terminal Block. The Terminal Blocks comes with hinged protective cover (shroud) that makes the Terminal Block shock proof (finger safe) and has marker recess to accept marking tag.

TECHNICAL DATA

Rated Voltage	1000 V
Rated Current	520 A
Housing Material	Polymide
Standard Colour	Grey
Product Function	Power Terminal Block
Wire Entry Orientation	Side Entry
Mounting Possibility	DIN 35/DIN 35-15 Rail
Stud Size	M16
Operated by	Nut Driver
Rated Surge Voltage	8 KV
Pollution Degree	3

CONNECTION DATA

Conductor Cross Section Stranded min.	25 mm ²
Conductor Cross Section Stranded max.	300 mm ²
Conductor Cross Section AWG/Kcmil min	2 AWG
Conductor Cross Section AWG/Kcmil max	1000 kcmil

DIMENSIONS

Height with DIN 35 x 15 mm rail	96.1 mm
Height with DIN 35 x 7.5 mm rail	88.6 mm
Length	218.6 mm
Width (Thickness)	55 mm

ORDERING INFORMATION

CAT. NO.	DESCRIPTION	STD. PACK
PTB300SH	300 sq.mm Stud Type Power Terminal Block in Grey colour	2


ACCESSORIES

IMAGES	CAT. NO.	DESCRIPTION	STD. PACK
	CA701-1M	Din 35 Rail unslotted 1 meter	50
	CA701-2M	Din 35 Rail unslotted 2 meter	50
	CA701-2M-S	Din 35 Rail slotted 2 meter	50
	CA701-1M-S	Din 35 Rail slotted 1 meter	50

ACCESSORIES

IMAGES	CAT. NO.	DESCRIPTION	STD. PACK
	CA701-15-1M	Din 35 Rail 15 deep unslotted 1 meter	50
	CA701-15-1M-S	Din 35 Rail 15 deep slotted 1 meter	50
	CA701-15-2M	Din 35 Rail 15 deep unslotted 2 meter	50
	CA701-15-2M-S	Din 35 Rail 15 deep slotted 2 meter	50
	CA102	End Clamp in Polyamide suitable for Din32 / Din35 / Din35-15 Rails	50
	CA202	End Clamp in Polyamide suitable for Din 35 / Din 35-15 Rails	25
	CA509/K16	Marking Tag Blank suitable for CTS35UNA / CGT35U Terminal Blocks	100
	CA703/13	Permanent Shorting Links for 2 way shorting.	10
	CA704/13	Permanent Shorting Links for 3 way shorting.	10

PTB300SH



connectwell
THE RIGHT CONNECTION

RATINGS AS PER STANDARDS

STANDARDS	UL 1059	IEC/EN60947-7-1
Conductor Cross Section Stranded min.	2 AWG	25 mm ²
Conductor Cross Section Stranded max.		300 mm ²
Rated Voltage	1000 V	1000 V
Rated Current	520 A	520 A
Tightening Torque	221 lb-in	25-35 Nm