


CPF4L


connectwell
 THE RIGHT CONNECTION

4 sq.mm push in Fuse compact Terminal Blocks

CP series Push-In Terminal Blocks have a specialised connection system that enables tool less wire connections. Reliable, vibration resistant, gas tight connections are made with inbuilt high quality stainless steel Push in spring clamps.

TECHNICAL DATA

Rated Voltage	1000 V
Rated Current	10 A
Housing Material	Polymide
Standard Colour	Grey
Product Function	Single Level Fuse with Indication
Wire Entry Orientation	Top
Mounting Possibility	DIN 35/DIN 35-15 Rail
Operated by	Screw Driver
Rated Surge Voltage	8 KV
Pollution Degree	3

CONNECTION DATA

Conductor Cross Section Stranded min.	0.2 mm ²
Conductor Cross Section Stranded max.	4 mm ²
Conductor Cross Section AWG/Kcmil min	24 AWG
Conductor Cross Section AWG/Kcmil max	10 AWG
Stripping Length	10 mm

DIMENSIONS

Height	68 mm
Length	54.8 mm
Width (Thickness)	6 mm

FUSE SPECIFICATIONS

Fuse Type	Glass type fuse
Fuse Size	5 X 20 mm
Fuse Current Rating	10 A

ORDERING INFORMATION

CAT. NO.	DESCRIPTION	STD. PACK
CPF4L6-60V	4mm ² Ø5X20mm PUSH IN FUSE TB 6-60V	50
CPF4L110-240V	4mm ² Ø5X20mm PUSH IN FUSE TB110-240V	50

ACCESSORIES

IMAGES	CAT. NO.	DESCRIPTION	STD. PACK
	CA701-1M	Din 35 Rail unslotted 1 meter	50
	CA701-2M	Din 35 Rail unslotted 2 meter	50

ACCESSORIES

IMAGES	CAT. NO.	DESCRIPTION	STD. PACK
	CA701-2M-S	Din 35 Rail slotted 2 meter	50
	CA701-1M-S	Din 35 Rail slotted 1 meter	50

	CA701-15-1M	Din 35 Rail 15 deep unslotted 1 meter	50
	CA701-15-1M-S	Din 35 Rail 15 deep slotted 1 meter	50
	CA701-15-2M	Din 35 Rail 15 deep unslotted 2 meter	50
	CA701-15-2M-S	Din 35 Rail 15 deep slotted 2 meter	50

	CA103	EndClamp in Polyamide suitable for Din 35/Din 35-15 rails	50
--	-------	---	----


	PPCX4/3	Partition Plate in Grey colour	50
--	---------	--------------------------------	----

	JX4/2	Shorting Link for 6 mm wide TB	100
	JX4/3	Shorting Link for 6 mm wide TB	50
	JX4/4	Shorting Link for 6 mm wide TB	50
	JX4/5	Shorting Link for 6 mm wide TB	50
	JX4/8	Shorting Link for 6 mm wide TB	10
	JX4/10	Shorting Link for 6 mm wide TB	10
	JX4/16	Shorting Link for 6 mm wide TB	10

	CA509/K6	Blank Marking Tag	100
--	----------	-------------------	-----

	SCS0.6/3.5	Electricians Screwdriver for slotted screws	10
--	------------	---	----

CPF4L



connectwell
THE RIGHT CONNECTION

RATINGS AS PER STANDARDS

STANDARDS	UL 1059	CSA C.22.2 No:158	IEC/EN60947-7-3
Approvals	UL	CSA	CE
Conductor Cross Section Stranded min.	24 AWG	24 AWG	0.2 mm ²
Conductor Cross Section Stranded max.	10 AWG	10 AWG	4 mm ²
Rated Voltage	600 V	600 V	1000 V
Rated Current	10 A	10 A	10 A